



Dow Performance Silicones

DOWSIL™ 813C Construction and Concrete Silicone Sealant

Specifically designed for interior and exterior applications in buildings and other types of construction

- Ideal for weatherseals, expansion and perimeter joint sealing
- Joint movement capability +/- 50%
- Conforms to ISO 11600-F-25LM
- Excellent weatherability, resistant to sunlight, ozone and extreme temperatures
- Good unprimed adhesion to a variety of porous and non-porous substrates, including concrete, masonry, brick, PVC-U, wood and some metals
- Easy to apply and excellent gun ability even at extreme temperatures


This color card is only intended for reference use.

Please contact your local Dow sales office or Dow distributor for more information about availability, packaging, lead time and prices.

Custom colors may be available upon request.




Black



White



German White



White Grey



Light Grey



Middle Grey



Brown



Bronze



Red Beige



Pink Coral




Desert Rose



Grey




Grey AV972




Stone



Sand



Champaign



Anthracite

Contact us

Dow is collaborating with industry professionals around the world to develop solutions to improve the energy efficiency of buildings for a more comfortable environment. Learn more about Dow's full range of High Performance Building solutions by visiting us online at consumer.dow.com/construction.

Dow has sales offices, manufacturing sites and science and technology laboratories around the globe. Find local contact information at consumer.dow.com/ContactUs.

DOWSIL™

silicones by 

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

*™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

© 2019 The Dow Chemical Company. All rights reserved.

S2D 91667/E88679

Form No. 62-1496-01 E